

Tentative

The Panasonic logo is located in the top right corner of the page. It consists of the word "Panasonic" in a white, sans-serif font, centered within a blue rectangular background that has a subtle gradient.

NCR20700B data sheet

Automotive & Industrial Systems Company of Panasonic Group
Portable Rechargeable Battery Business Division, SANYO Electric Co., Ltd.

Specifications for NCR20700B

Specifications		
Rated capacity ⁽¹⁾		4000mAh
Capacity ⁽²⁾	Minimum	4050mAh
	Typical	4250mAh
Nominal voltage		3.6V
Charging	Method	CC-CV
	Voltage	4.20V
	Current	Std. 2000mA
	Time	Std. 180min.
Weight (max.)		63.0g
Temperature	Charge	10 to +45° C
	Discharge	-20 to +60° C
	Storage	-20 to +50° C
Energy density ⁽³⁾	Volumetric	659 Wh/l
	Gravimetric	224 Wh/kg

Dimensions		
With tube	H	Max. 70.3mm
	D	Max. 20.35mm
	d	Max. 10.5mm

⁽¹⁾ At 20° C ⁽²⁾ At 25° C


⁽³⁾ Energy density is calculated using bare cell dimensions (without tube).

When designing a pack, refer to the cell's mechanical drawing for precise dimensions.

<Remark> These values are not guaranteed values.



Discharge rate Characteristics for NCR20700B




<Remark> These values are not guaranteed values.



[4A discharge]

Charge :CC-CV:2A - 4.2V(80mA cut) at 25°C
Discharge:CC:4A to 2.5V at 25°C,10°C,0°C,-10°C




<Remark> These values are not guaranteed values.



[20A discharge]

Charge :CC-CV:2A - 4.2V(80mA cut) at 25°C
Discharge:CC:8A to 2.5V at 25°C,10°C,0°C,-10°C




<Remark> These values are not guaranteed values.



Cycle Characteristics for NCR20700B

< Without Temp. cut cycle performance of single cell >



<Remark> These values are not guaranteed values.

Panasonic

ideas for life